


## 1080P AHD/TVI/CVI Hybrid Bullet Camera

|   |   |
|---|---|
|  | <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>✧ Full HD 1920x1080P@25/30fps Color Camera</li> <li>✧ 1/2.9" 2M CMOS Sensor</li> <li>✧ Color: 0.1Lux@F2.0, IR On: 0Lux</li> <li>✧ Video Output: AHD, TVI, CVI or CVBS Switchable</li> <li>✧ Digital WDR</li> <li>✧ 2D/3D Noise Reduction</li> <li>✧ Smart IR</li> </ul> |
|---|---|

| <b>MODEL</b> |                                  | <b>AV-S221</b>                      |
|--------------|----------------------------------|-------------------------------------|
| Video        | Image Sensor                     | 1/2.9" 2M CMOS Sensor               |
|              | Video Frame Rate (Maximum)       | 1920x1080p@25/30fps                 |
|              | Minimum Illumination             | Color: 0.1Lux@F2.0, IR On: 0Lux     |
|              | Video Output                     | AHD, TVI, CVI or CVBS Switchable    |
|              | Mechanical IR Cut Filter (ICR)   | Yes                                 |
|              | IR LED; Working Distance (Meter) | 6pcs Array High Power LEDs ; 20-25M |
|              | S/N Ratio                        | More Than 50dB (AGC Off)            |
|              | OSD Menu                         | Via CoC Control                     |
|              | Day & Night Mode                 | Smart IR                            |
|              | Auto Electronic Shutter          | Auto 1/25 (1/30~1/50,000 Sec)       |
|              | White Balance                    | AWB/ATW/AWC                         |

|          |                             |  |
|----------|-----------------------------|--|
| Function | WDR                         | D-WDR  |
|          | Dynamic Noise Reduction     | 2D/3D  |
|          | Lens Shading Compensation   | Yes  |
|          | Language                    | English, Chinese, Russian, Portuguese, Spanish |
| General  | Lens Mount                  | M12  |
|          | Lens, Angle of View         | Standard f3.6mm; Option: f6.0mm                |
|          | Water Resistance            | IP66   |
|          | Power Supply; Consumption   | 12Vdc; 5.0W                                    |
|          | Operation; Storage Temp     | -10°C ~ 50°C; -20°C ~ 60°C                     |
|          | Operation; Storage Humidity | Maximum: RH80%; RH90%                          |
|          | Dimensions (mm)             | 84.8 (W)× 73.8 (H)×121 (L)                     |
|          | Net Weight                  | 380g   |